

1.67 BLUECUT



BLUE
CUT



THINNER
AND LIGHTER



UV - 410 NM
PROTECTION

PERFECT
COMBINATION
OF TECHNOLOGY
AND ESTHETIC



VIDCON

1.67 BLUECUT

VIDCON

TOOLING INDEX: 1.530

Nominal Curve	Dia	True Front Curve		Radius of Curvature	Sag 40mm	Sag 50mm	Back Curve	C.T.	E.T.
		by index 1.665	by index 1.530						
0,50	75	0,59	0,47	1127,12	0,18	0,28	9,50	6,0	16,3
1,00	75	1,70	1,35	391,20	0,51	0,80	8,10	7,0	14,3
2,00	75	2,38	1,90	279,53	0,71	1,12	6,75	7,0	11,9
3,00	75	3,68	2,93	180,82	1,10	1,74	5,40	7,0	8,9
4,00	75	4,26	3,40	156,10	1,27	2,01	5,40	7,0	8,3
5,00	75	4,87	3,88	136,58	1,45	2,31	5,40	7,5	8,1
6,00	75	6,10	4,86	108,98	1,82	2,91	6,75	7,5	8,3
7,00	75	7,37	5,88	90,18	2,20	3,53	6,75	7,8	7,0
8,00	75	8,35	6,65	79,68	2,49	4,02	6,75	9,0	7,0
9,00	75	9,63	7,67	69,09	2,87	4,68	8,10	8,7	7,0
10,00	70	10,73	8,55	62,00	3,21	5,26	8,10	10,0	7,0
11,00	70	11,52	9,18	57,73	3,45	5,69	8,10	10,0	6,0
13,00	70	13,82	11,01	48,13	4,16	7,00	9,50	11,7	6,0

1.67 SFSV 75/70mm Blue Cut